CERES UPLIGHTER PENDANT CEILING MOUNTING PLATE

FINISH

antique bronze bronze

DIMENSIONS (body of fixture)

 $996 \times 920 \times 75 \text{ mm} (l \times w \times h)$

WEIGHT

10kg (22lbs)

please ensure ceiling structure is strong enough to support the weight of the light

OVERALL DROP

minimum 232 mm

maximum on request 8082 mm

supplied with 1000mm drop rod (16 mm dia) as standard (adjustable on site)

ILLUMINATION

220-240v - integrated LED - 110w - 2700k 110-130v - integrated LED - 110w - 2700k LED driver to be installed in the ceiling cavity or remote drivers must be installed up to 20 meters from the body of the light

DIMMING

trailing dimmable / phase cut (rotary dimmer) - standard DALI option available (220-240v only) 0/1-10v (220-240v) - on request


CEILING ROSE / PLATE


ceiling plate - 180mm x 180mm x 7mm


CERTIFICATION













^{*}Diagrams are not to scale.

CERES UPLIGHTER PENDANT CEILING ROSE

FINISH

antique bronze bronze

DIMENSIONS (body of fixture)

 $996 \times 920 \times 75 \text{ mm} (l \times w \times h)$

WEIGHT

10kg (22lbs)

please ensure ceiling structure is strong enough to support the weight of the light

OVERALL DROP

minimum 290 mm maximum on request 8140 mm supplied with 1000mm drop rod (16 mm dia) as standard (adjustable on site)

ILLUMINATION

220-240v - integrated LED - 110w - 2700k 110-130v - integrated LED - 110w - 2700k LED driver to be installed in the ceiling rose

DIMMING

trailing dimmable / phase cut (rotary dimmer) - standard DALI option available (220-240v only) 0/1-10v (220-240v) - on request


CEILING ROSE / PLATE


ceiling rose - 240mm x 240mm x 65mm


CERTIFICATION













^{*}Diagrams are not to scale.

CERES UPLIGHTER PENDANT CEILING MOUNTING PLATE - DALI A

FINISH

antique bronze bronze

DIMENSIONS (body of fixture)

996 x 920 x 75 mm (l x w x h)

WEIGHT

10kg (22lbs)

please ensure ceiling structure is strong enough to support the weight of the light

OVERALL DROP

minimum 253 mm maximum on request 8103 mm supplied with 1000mm drop rod (16 mm dia) as standard (adjustable on site)

ILLUMINATION

220-240v - integrated LED - 110w - 2700k DALI LED driver to be installed in the ceiling cavity or remote drivers must be installed up to 20 meters from the body of the light

DIMMING

DALI Compatible

CEILING ROSE / PLATE


ceiling plate - 180mm x 180mm x 7mm


CERTIFICATION



















^{*}Diagrams are not to scale.

CERES UPLIGHTER PENDANT CEILING ROSE - DALI A

FINISH

antique bronze bronze

DIMENSIONS (body of fixture)

996 x 920 x 75 mm (l x w x h)

WEIGHT

10kg (22lbs)

please ensure ceiling structure is strong enough to support the weight of the light

OVERALL DROP

minimum 290 mm maximum on request 8140 mm supplied with 1000mm drop rod (16 mm dia) as standard (adjustable on site)

ILLUMINATION

220-240v - integrated LED - 110w - 2700k DALI LED driver to be installed in the ceiling rose

DIMMING

DALI compatible

CEILING ROSE / PLATE


ceiling rose - 240mm x 240mm x 65mm


CERTIFICATION















^{*}Diagrams are not to scale.



CERES UPLIGHTER PENDANT

SKU NUMBER	FINISH DESCRIPTION	VOLTAGE
CERPEUAB-CM-240	antique bronze	220 - 240V
CERPEUAB-CM-DALIA-240	antique bronze	220 - 240V
CERPEUAB-CM-110	antique bronze	110 - 130V
CERPEUBZ-CR-240	bronze	220 - 240V
CERPEUBZ-CR-DALIA-240	bronze	220 - 240V
CERPEUBZ-CR-110	bronze	110 - 130V